

- Fire alarm systems, 760.26, 760.27, 760.52
- Fixture wires, Art. 402
- In free air, Tables 310.17, 310.19, 310.20
- Gauges (AWG), general provisions, 110.6
- General wiring, Art. 310
- Generators, size, 445.13
- Grounded
  - Alternating current systems, 250.24, 250.26
  - Identification, 200.6, 200.7, 210.5(A)
  - Change in size, 240.23
  - Continuity of, 300.13(B)
  - Definition, Art. 100-I
  - Different systems, 200.6(D)
  - Electrode-type boilers, over 600 volts, 490.72(E)
  - Fuses in, 430.36
  - Overcurrent protection, 230.90(B), 240.22
  - Separately derived systems, 250.30(A)
  - Services
    - Disconnection of, 230.70, 230.75
    - Overcurrent protection, 230.90(B)
    - Switches, disconnection, 404.2(B)
    - Use and identification, Art. 200
- Grounded power systems in anesthetizing locations, 517.63
- Grounding. *see* Grounding conductors
- Grounding electrode. *see* Grounding electrode conductors
- Grouped
  - Definition, 520.2
  - Identification, 310.12
- Induction and dielectric heating equipment, ampacity of supply, 665.10
- Industrial control panels, 409.20
- Installation with other systems, 300.8
- Insulated
  - Definition, Art. 100-I
- Insulating materials, 310.13
- Insulation, Art. 310
  - At bushings, 4 AWG and larger, 300.4(F), 312.6(C)
  - Construction and application, 310.13
  - Elevators, dumbwaiters, escalators, moving walks, wheelchair lifts, and stairway chair lifts, 620.11
  - Fire alarm systems, 760.27(B)
  - Fixtures, 410.24, 410.67
  - Hazardous (classified) locations, 501.13, 501.20, 505.18(B)
  - Identification, 310.12
  - Line-type fire detectors, 760.82(J)
  - Marking, 310.11
  - Motion picture projectors, 540.14
  - Service conductors, 230.22, 230.30, 230.41
  - Splices and joints, 110.14(B), 400.9, 530.12, 590.4(G)
  - Switchboards, 408.19
  - Theaters, 520.42
  - Intrinsically safe, 504.30, 504.50
  - Length in boxes, 300.14
  - Length in transient voltage surge suppressors, 285.12
  - Lightning rods, spacing from, 250.106, 800.53, 820.44(F)(3)
  - Liquidtight flexible metal conduit. *see* Liquidtight flexible metal conduit
  - Liquidtight flexible nonmetallic conduit. *see* Liquidtight flexible nonmetallic conduit
  - Metal-clad cable. *see* Metal-clad cable
  - Metal enclosures, spacing from lightning rods, 250.106 FPN No. 1 and No. 2
  - Mineral-insulated metal-sheathed cable. *see* Mineral-insulated metal-sheathed cable (Type MI)
  - Minimum size, 230.42, 310.5, 517.74(B), 620.12, 650.6(A), 660.9, 725.27(A), 760.27(A), 760.57, 810.17
  - Motion picture projectors, sizes, 540.13
  - Motor circuits, 430-II
  - Multioutlet assembly. *see* Multioutlet assembly
  - Multiple, 250.30(A)(8)(b), 250.102(C), 250.122(F), 300.20, 310.4, 392.8(D), 520.27(A)(2), 620.12(A)(1)
  - Nonmetallic extensions. *see* Nonmetallic extensions
  - Nonmetallic sheathed cable, Types NM, NMC, and NMS. *see* Nonmetallic-sheathed cable (Types NM, NMC, and NMS)
  - Number of, in. *see* Conductor fill
  - Organs, 650.6, 650.7
  - Outlet boxes, temperature limits, 410.11
  - Outside wiring, Art. 225
  - Overcurrent protection, 240.3, 240.4
    - Cablebus conductors, 370.5
    - Grounded conductors, 230.90(B), 240.22
    - Service-entrance conductors, 230.90, 230.91, 230.208
  - Overhead, 800.44
  - Over 600 volts, Art. 490
  - Paralleled, 250.30(A)(8)(b), 250.102(C), 250.122(F), 300.20, 310.4, 392.8(D), 520.27(A)(2), 620.12(A)(1)
  - Pendant fixtures, 410.27
  - Properties of, Chap. 9, Table 8
  - Raceways, number of conductors in. *see* Conductor fill
  - Radio and television
    - Antenna distribution systems, 810.4, Art. 820
    - Antenna systems, Art. 810
    - Equipment, Art. 810
  - Railway, power and light from, 110.19
  - Recreational vehicle site feeder circuit, 551.73, 551.80
    - Definition, 551.2
  - Remote-control circuits, Art. 725
  - Rigid metal conduit. *see* Rigid metal conduit
  - Same circuit, 300.5(I)
  - Selection of, examples, Annex D
  - Service. *see* Service-entrance cable (Types SE and USE); Service-entrance conductors
    - Definition, Art. 100-I
  - Service-entrance. *see* Service-entrance conductors
  - Signal circuits, Art. 725, Art. 760
  - Signs and outline lighting, 600.31, 600.32
  - Single, 392.8(E), 392.10, 392.11(B), 392.13(B)
  - Sizes, 110.6, Chap. 9, Tables 5 and 5A. *see also subhead: Minimum size*
  - Spliced, 230.33, 230.46
  - Stranded, 310.3
  - Support of, in vertical raceways, 300.19
  - Surface raceway. *see* Strut-type channel raceway; Surface metal raceways; Surface nonmetallic raceways
  - Switchboards and panelboards, 408.3(A), 408.19
  - Temperature, limitations of, 310.10, 338.10(B)(3)
  - Theaters, portable stage equipment, 520.68
  - Underfloor raceway. *see* Underfloor raceways
  - Underground feeder and branch-circuit cable. *see* Underground feeder and branch-circuit cable (Type UF)
  - Ungrounded
    - Identification, 210.5(C)
    - Services, 230.90(A)
    - Tapped from grounded system, 210.10
  - Welders, electric
    - Ampacity of supply, 630.11, 630.31
    - Overcurrent protection, 630.12(B), 630.32(B)
    - Wet locations, 225.4, 310.8(C), Table 310.13
    - Wireways. *see* Wireways, metal; Wireways, nonmetallic
    - X-ray equipment, 517-V, 660.6 through 660.9
  - Conduit bodies.** *see also* Boxes (outlet, device, pull, and junction)
    - Definition, Art. 100-I
    - Number of conductors, 314.16(C)
    - Pull and junction box, 314.28
    - Short radius, 314.5
    - Support of, by rigid nonmetallic conduit, 352.10(H)
  - Conduit fill.** *see also* Conductor fill
    - Equipment grounding conductors, Chap. 9, Note 3 to Table 1
    - Grounding conductor, 310.15(B)(5)
  - Conduit nipples,** Chap. 9, Note 4 to Table 1
  - Conduits**
    - Boxes supporting, 314.23(H)(2)
    - Circuits, physical protection of remote control, 725.11(B)
    - Conductors, number in, Chap. 9, Table 1, Annex C, Tables C1 through C12(A)
    - Dimensions, Chap. 9, Table 4
    - Electrical metallic tubing. *see* Electrical metallic tubing
    - Electrical nonmetallic tubing. *see* Electrical nonmetallic tubing
    - Flexible metal. *see* Flexible metal conduit
    - High density polyethylene conduit (Type HDPE). *see* High density polyethylene conduit (Type HDPE)
    - Intermediate metal. *see* Intermediate metal conduit
    - Liquidtight flexible metal. *see* Liquidtight flexible metal conduit
    - Liquidtight flexible nonmetallic. *see* Liquidtight flexible nonmetallic conduit
    - Metallic, grounding runs 7.5 m (25 ft), 250.86 Ex.1
    - Number of fixture wires in, 402.7
    - Outside wiring, 225.10
    - Rigid metal. *see* Rigid metal conduit
    - Rigid nonmetallic. *see* Rigid nonmetallic conduit
  - Connections**
    - Aluminum, copper conductors, 110.14