

- Theater dressing rooms, 520.72
- Lamp wattage, marking on luminaire (fixture), 410.70
- Medium and mogul bases, 410.53
- Snap switches for, 404.14(B)(3)
- Independent**
  - Circuits for emergency lighting, 700.17
  - Supports, services, over buildings, 230.29
  - Wiring, emergency circuits, 700.9(B)
  - X-ray control, 660.24
- Individual branch circuits.** *see* Branch circuits, individual
- Induced currents, metal enclosures,** 300.20, 330.31
- Induction and dielectric heating equipment,** Art. 665
  - Ampacity of supply conductors, 665.10
  - Definitions, 665.2
  - Disconnecting means, 665.12
  - Guarding, grounding, and labeling, 665-II
    - Access to interior equipment, 665.22
    - Capacitors, 665.24
    - Component interconnection, 665.19
    - Control panels, 665.21
    - Enclosures, 665.20
    - Grounding and bonding, 665.26
    - Marking, 665.27
    - Shielding, 665.25
    - Warning labels or signs, 665.23
  - Hazardous (classified) locations, 665.4
  - Output circuits, 665.5
  - Overcurrent protection, 665.11
  - Remote control, 665.7
- Induction heating**
  - Definition, 665.2
- Inductive loads**
  - Motors, 430.83, 430.109
  - Signs, 600.6(B)
  - Switches, types, ratings, 404.14
- Industrial control panels,** Art. 409
  - Conductors
    - Busbars, 409.102
    - Minimum size and ampacity, 409.20
  - Construction specifications, 409-III
  - Definition, 409.2
  - Disconnecting means, 409.30
  - Enclosures, 409.100
  - Flash protection, 110.16
  - Grounding, 409.60
  - Installation, 409-II
  - Marking, 409.110
  - Overcurrent protection, 409.21
  - Service equipment, 409.108
  - Spacing, minimum, 409.106
  - Wiring space in, 409.104
- Industrial machinery,** Art. 670
  - Definition, 670.2
- Disconnecting means, 670.4(B)
- Nameplates, 670.3
- Supply conductors and overcurrent protection, 670.4
- Industrial manufacturing system**
  - Definition, 670.2
- Information technology equipment,** Art. 645
  - Cables not in information technology equipment rooms, 645.6
  - Disconnecting means, 645.4(1), 645.10
  - Grounding, 645.15
  - Marking, 645.16
  - Penetrations, 645.7
  - Power distribution units, 645.17
  - Special requirements for information technology equipment rooms, 645.4
  - Supply circuits and interconnecting cables, 645.5
  - Uninterruptible power supplies (UPS), 645.11
- Infrared lamp industrial heating appliances,** 422.14, 422.48
  - Branch circuits, 210.23(C), 422.11(C), 424.3(A)
  - Overcurrent protection, 422.11(C)
- Inhalation anesthetizing locations.** *see* Anesthetizing locations
- Inserts**
  - Cellular concrete floor raceways, 372.9
  - Cellular metal floor raceways, 374.10
  - Underfloor raceways, 390.14
- In sight from**
  - Air-conditioning or refrigerating equipment, 440.14
  - Center pivot irrigation machines, 675.8(B)
  - Definition, Art. 100-I
  - Duct heaters, 424.65
  - Electric-discharge lighting, 410.81(B)
  - Fixed electric space heating equipment, 424.19(A)
  - Motor driven appliances, 422.32
  - Motors, motor controllers, 430.102
  - Room air conditioners, 440.63
  - Signs, 600.6(A)
- Institutions, emergency lighting,** Art. 700
- Instructions,** 110.3(B), 230.95(C)
- Instrumentation tray cable (Type ITC),** Art. 727
  - Allowable ampacity, 727.8
  - Bends, 727.10
  - Construction, 727.6
  - Definition, 727.2
  - Marking, 727.7
  - Overcurrent protection, 727.9
  - Uses not permitted, 727.5
  - Uses permitted, 727.4
- Instruments, meters, relays**
  - Grounding, 250-IX
- Hazardous (classified) location, 501.105, 502.150
- Low-voltage, 517.64
- Instrument transformers.** *see* Transformers, instrument, grounding
- Insulation**
  - Conductors. *see* Conductors, insulation
  - Double. *see* Double insulated Equipment, 110.3(A)(4)
  - Fixture wire, 402.3, Table 402.3
  - Flexible cords, 400.4, Table 400.4, 400-II
  - Heating cables, 424-V
  - Integrity, 110.7
- Insulation levels**
  - Definitions, 100 percent, 133 percent, Table 310.64
- Insulators**
  - Nonabsorbent, 230.27, 394.30(A)
  - Open wiring. *see* Open wiring on insulators
- Integrated electrical systems,** Art. 685
  - Applications of other articles, 685.2
  - DC system grounding, 685.12
  - Orderly shutdown, 645.10 Ex., 645.11, 685-II
  - Overcurrent protection, location of, 685.10
  - Ungrounded control circuits, 685.14
- Integrated gas spacer cable (Type IGS),** Art. 326
  - Construction, 326-III
  - Conductors, 326.104
  - Conduit, 326.116
  - Insulation, 326.112
  - Marking, 326.120
  - Definition, 326.2
  - Installation, 326-II
    - Ampacity, 326.80
    - Bending radius, 326.24
    - Bends, 326.26
    - Fittings, 326.40
    - Uses not permitted, 326.12
    - Uses permitted, 326.10
- Interactive systems**
  - Definition, 690.2, 705.2
  - Fuel cell systems, connection to, 692-VII
- Intercommunications systems.** *see* Communications circuits; Hazardous (classified) locations
- Interconnected electric power production sources,** Art. 705
  - Connection point, 705.12
  - Definition, 705.2
  - Directory, 705.10
  - Disconnect device, 705.22
  - Disconnecting means, equipment, 705.21
  - Disconnecting means, sources, 705.20
  - Ground-fault protection, 705.32
  - Grounding, 705.50
- Interrupting and short-circuit current rating, 705.16
- Loss of primary source, 705.40
- Output characteristics, 705.14
- Overcurrent protection, 705.30
- Point of connection, 705.12
- Synchronous generators, 705.43
- Unbalanced interconnections, 705.42
- Intermediate metal conduit (Type IMC),** Art. 342
  - Bends, 342.24, 342.26
  - Bushings, 342.46
  - Construction, 342-III
  - Couplings and connectors, 342.42
  - Definition, 342.2
  - Dissimilar metals, 342.14
  - Installation, 342-II
  - Listing, 342.6
  - Maximum number of conductors and fixture wires in, Tables C4 and C4A
  - Number of conductors, 342.22
  - Reaming and threading, 342.28
  - Size, 342.20
  - Splices and taps, 342.56
  - Standard lengths, 342.130
  - Supports and securing, 342.30
  - Uses permitted, 342.10
  - Wet locations, 342.10(D)
- Intermittent duty**
  - Definition, Art. 100-I
  - Motors, 430.22(E)
- Interpretations, formal.** *see* Formal interpretations
- Interrupter switch.** *see* Switches, interrupter
- Interrupting rating,** 110.9, 240.60(C)(3), 240.83(C)
  - Definition, Art. 100-I
- Intrinsically safe apparatus**
  - Definition, 504.2
  - Grounding, 504.50(A)
- Intrinsically safe circuits**
  - Definition, 504.2
  - Different
    - Definition, 504.2
- Intrinsically safe systems,** Art. 504
  - Bonding, 504.60
  - Conductors, separation of, 504.30
  - Definitions, 504.2
  - Equipment installation, 504.10, 506.8(C)
  - Equipment listing, 504.4
  - Grounding, 504.50
  - Identification, 504.80
  - Sealing, 504.70
  - Separation of intrinsically safe conductors, 504.30
  - Wiring methods, 504.20
- Introduction,** Art. 90
- Inverter**
  - Definition, 690.2
- Irons.** *see* Flatirons
- Irrigation machines,** Art. 675
  - Bonding, 675.14
  - Center pivot, 675-II
  - Definition, 675.2